



686 S. Adams
 Kansas City, KS. 66105
 (913) 321-9000

Raven® 950

Lubricating Flushing Agent

Technical Data Sheet

Selection & Specification Data									
<p>Description</p> <p>Raven 950 is a lubricating flushing agent that can be used to flush and store components of epoxy, polyurea or polyurethane plural component spray systems. Raven 950 can be used as a lubricating agent in wet cups to lubricate the displacement rod and extend the life of the spray equipment packings.</p> <p>Effective with</p> <ul style="list-style-type: none"> • Compatible with epoxy coatings • Compatible with Polyurea coatings • Compatible with Polyurethane Spray foam, or coatings • Compatible with Polyaspartic coatings <p>Advantages:</p> <ul style="list-style-type: none"> • Non toxic & non-chlorinated • Non-flammable • Easy to use • Flash point >200°F • Low odor • Indefinite shelf life • Will not cause hazardous polymerization • Low evaporation rate 	<p>Physical Properties (Typical) Independent Testing</p> <table border="1"> <tr> <td>Color</td> <td>Clear liquid</td> </tr> <tr> <td>Specific Gravity @ 25°C</td> <td>1.1 @ 77°F</td> </tr> <tr> <td>Flash Point</td> <td>>200°F</td> </tr> <tr> <td>Odor</td> <td>Mild, Sweet Odor</td> </tr> </table> <p>Preparation & Application</p> <p>Raven 950 is recommended for single use only. Keep stored in tightly seal container to prevent moisture contamination. Raven 950 may be left in the feed lines, hoses, and wet cups until next time equipment is used.</p> <p>Safety</p> <p>Safety - Review SDS at www.ravenlining.com.</p> <ul style="list-style-type: none"> • Wear Long sleeve overalls or disposable Tyvex suit • Rubber gloves • Protective eye wear • Rubber or leather boots • Respirator • Do not use near high heat or open flame • Do not take internally • Keep out of reach of children 	Color	Clear liquid	Specific Gravity @ 25°C	1.1 @ 77°F	Flash Point	>200°F	Odor	Mild, Sweet Odor
Color	Clear liquid								
Specific Gravity @ 25°C	1.1 @ 77°F								
Flash Point	>200°F								
Odor	Mild, Sweet Odor								
Packaging, Handling, & Storage									
<p>Packaging</p> <p>Available in 1,5, and 55 gallon containers.</p>	<p>Shelf Life</p> <p>One year from shipment date, in original, unopened factory containers.</p> <p>Storage Temperature & Humidity</p> <p>Under normal storage conditions of 70°F to 95°F (21° - 35°C).</p>								
Precautions									
<p>This product contains Volatile Organic Compounds (VOC's) which may be released during and for some period after installation producing odors and affecting air quality. To avoid possible contamination of sensitive substances and for protection of human health, ensure proper air ventilation of work areas until odors completely dissipate.</p>									



Raven® 950

Flushing Agent
Technical Data Sheet

Warranty

Limited Warranty. Company warrants its goods to be free of manufacturing defects. Goods manufactured by Company will comply with all applicable federal, state and local laws and regulations. Company makes no warranty as to any parts or equipment manufactured by others. Customer shall look solely and only to the manufacturer of such parts or equipment with respect to any warranty claims. Company hereby assigns to Customer the original manufacturer's warranties to all such equipment and parts, to the full extent permitted. THE AFORESAID IS THE EXCLUSIVE WARRANTY AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. SPECIFICALLY, THERE ARE NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

Limitation of Liability. COMPANY'S LIABILITY FOR DEFECTIVE OR NON-CONFORMING GOODS SHALL BE LIMITED TO, AND SHALL IN NO EVENT EXCEED, THE AMOUNT PAID BY CUSTOMER FOR SUCH DEFECTIVE OR NON-CONFORMING GOODS. UNDER NO CIRCUMSTANCES SHALL COMPANY BE LIABLE FOR ANY SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR FOR LOST PROFITS. In no event may any claim by Customer arising from or relating to any sale of any goods or services referenced herein be brought more than one year after the date of delivery of such Goods.